


1.44-Inch HD IPS TFT LCD



This IPS TFT display is controlled via SPI. Therefore, it is suitable for the use as an output device for microcontrollers (e.g. NodeMCU, ES-P8266) and single-board computers (e.g. Raspberry Pi). By using a high-resolution IPS panel with a pixel density of 125 Dpi, content can be displayed in high-resolution on the compact display.

	-	45 38	
1000	- 62 - 62 - 6 - 6 - 6 - 6 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7		32.5
			1.5

Published: 15.01.2024

MAIN FEATURES				
Туре	Full color IPS TFT LCD with			
	white LED backlight			
Resolution	128 x 128 Pixel			
Colors	18-bit color depth			
	(262.144 colors)			
Control chip	ILI9163			
Digital Interface	SPI			
Special feature	Via pin controllable back-			
	light			
Dimensions	30 x 43 x 10 mm			
Items delivered	SBC-LCD02 with pins			

FURTHER SPECIFICATIONS				
Voltage supply	3.3V			
Logic level	3.3 V			
Pixel density	125 Dpi			
Operation temperature	-40 °C - 85 °C			

FURTHER DETAILS				
Article No.	SBC-LCD02			
EAN:	4250236821986			
Customs Tariff No.	8473302000			

